



CONDUCTORES RG S.R.L.

MULTIFILARES EXTRAFLEXIBLES | MALLAS PLANAS Y REDONDAS BRAID AND BARE CABLES | ROUND AND FLAT BRAIDS

Desnudos extraflexibles acorde a DIN 46438
Extraflexibles according to DIN 46438

Diámetro de Alambre mm <i>Wire Diameter mm</i>	0.07 +/- 0.04
Material <i>Material</i>	E-Cu OF-Cu:

Información Técnica *Technical Information*

Sección Nominal mm ² <i>Section in mm²</i>	Nº de Alambres tol +/- 1% <i>Nº of Wires tol +/- 1%</i>	Ancho mm <i>Wide mm</i>	Espesor mm <i>Thickness mm</i>	Peso Kg/1000 mt <i>Weight Kg/1000 mt</i>	Nº de Capas <i>Nº of Layers</i>
0.5	132	2.5	0.4	5.0	1
1.0	264	3.2	0.7	10.0	
1.5	384	4.0	0.8	15.0	
2.0	528	5.0	0.8	20.0	
2.5	648	5.8	0.8	25.0	
3.0	792	7.5	0.9	30.0	
4.0	1056	8.2	1.0	40.0	

Referencias:

E-Cu: electrolítico | OF-Cu: Cobre Libre De Oxígeno

References:

E-Cu: Electrolytic Copper | OF-Cu: Oxygen Free Copper