



CONDUCTORES RG S.R.L.

## MULTIFILARES EXTRAFLEXIBLES | CABLES MULTIFILARES DE COBRE

*BRAID AND BARE CABLES | TWISTED CABLES*

**Desnudos Extraflexibles acorde a DIN 46438**  
*Extraflexibles according to DIN 46438*

Diámetro de Alambre mm <i>Wire Diameter mm</i>	0.05 +/- 0.004
Material <i>Material</i>	E-Cu   OF-Cu

### Información Técnica

*Technical Information*

Diámetro Exterior mm <i>Outside Diameter mm</i>	Nº de Alambres tol +/- 1% <i>Nº of Wires tol +/- 1%</i>	Sección Nominal mm <sup>2</sup> <i>Section in mm<sup>2</sup></i>	Peso Kg/1000 mt <i>Weight Kg/1000 mt</i>
0.6	108	0.2	2.0
0.8	180	0.35	3.5
1.0	266	0.5	5
1.2	392	0.75	7.5
1.4	672	1.32	13.2
1.7	910	1.78	17.8
1.75	980	1.92	19.2
2.2	1288	2.52	25.2
2.5	1666	3.27	32.7
2.6	1820	3.57	35.7
3.5	3087	6.06	60.6

**Referencias:**

E-Cu: Cobre Electrolítico | OF-Cu: Cobre Libre De Oxígeno

**References:**

E-Cu: *Electrolytic Copper* | OF-Cu: *Oxygen Free Copper*