



CONDUCTORES RG S.R.L.

MULTIFILARES EXTRAFLEXIBLES | CABLES TRENZADOS DE COBRE BRAID AND BARE CABLES | STRANDED ROUND CABLES

Desnudos extraflexibles acorde a DIN 46438
Extraflexibles according to DIN 46438

Diámetro de Alambre mm <i>Wire Diameter mm</i>	0.10 +/- 0.004
Material <i>Material</i>	E-Cu OF-Cu

Información Técnica *Technical Information*

Diámetro Exterior mm <i>Outside Diameter mm</i>	Nº de Alambres tol +/- 1% <i>Nº of Wires tol +/- 1%</i>	Sección Nominal mm ² <i>Section in mm²</i>	Peso Kg/1000 mt <i>Weight Kg/1000 mt</i>
2.0	255	2.0	20.0
2.2	289	2.2	22.0
2.4	306	2.4	24.0
2.6	360	2.8	28.0
2.8	432	3.4	34.0
3.3	504	3.9	39.0
3.5	648	5.0	50.0
4.0	820	6.4	64.0
5.0	2550	20.0	200.0

Referencias:

E-Cu: Cobre Electrolítico | OF-Cu: Cobre Libre De Oxígeno

References:

E-Cu: Electrolytic Copper | OF-Cu: Oxygen Free Copper